

<b>1.</b>	<b>GENERAL INFORMATION</b>		
1.1	Date updated:	12/9/2025	
1.2	Vessel's name (IMO number):	VASILIKI (9344588)	
1.3	Vessel's previous name(s) and date(s) of change:	SÜRMENE KA	
1.4	Date delivered/Builder (where built):	12.05.2005 / YANGZHOU KEIJIN SHIPYARD-JIANGGU/CHINA	
1.5	Flag/Port of Registry:	GREECE/Piraeus	
1.6	Call sign/MMSI:	SVCT5/241597000	
1.7	Vessel's contact details (satcom/fax/email etc.):	pp.vasiliki@gmail.com / +30 6943055887	
1.8	Type of vessel (as described in Form A or Form B Q1.11 of the IOPPC):	Oil Tanker	
1.9	Type of hull:	Double Hull/Double bottom	
<b>Ownership and Operation</b>			
1.10	Registered owner - Full style:	SEKA 02 Maritime Company 53-55 Akti Miaouli Str. 185 36, PIRAEUS Tel: +30 210 4239160 Fax: +30 210 4293345+ E-mail: sekasales@seka.gr Web: www.seka.gr Vat #:999416313, DOY PLOION PEIRAIA	
1.11	Technical operator - Full style:	MASTER MARIN SHIPPING COMPANY SHIP MANAGERS – OPERATORS 1ST FLOOR, 4-6, BOUBOULINAS str., PC – 18755 PIRAEUS, ATHENS – GREECE EMAIL – mastermarine.shipping@gmail.com	
1.12	Commercial operator - Full style:	MASTER MARIN SHIPPING COMPANY SHIP MANAGERS – OPERATORS 1ST FLOOR, 4-6, BOUBOULINAS str., PC – 18755 PIRAEUS, ATHENS – GREECE EMAIL – mastermarine.shipping@gmail.com	
1.13	Disponent owner - Full style:	MASTER MARIN SHIPPING COMPANY SHIP MANAGERS – OPERATORS 1ST FLOOR, 4-6, BOUBOULINAS str., PC – 18755 PIRAEUS, ATHENS – GREECE EMAIL – mastermarine.shipping@gmail.com	
<b>Insurance</b>			
1.14	P & I Club - Full Style:	SHIPOWNERS - White Chapel Building, 2nd Floor 10 Whitechapel High Street London E1 8QS T +44 207 488 0911 F +44 207 480 5806 W www.shipownersclub.com	
1.15	P & I Club pollution liability coverage/expiration date:	1,000,000,000 US\$	Feb 04, 2023
1.16	Hull & Machinery insured by - Full Style: (Specify broker or leading underwriter)		
1.17	Hull & Machinery insured value/expiration date:		
<b>Classification</b>			
1.18	Classification society:	INSB	
1.19	Class notation:	1+HULL+MACH, OIL TANKER ESP ; CHEMICAL TANKER ESP UNRESTRICTED NAVIGATION	
1.20	Is the vessel subject to any conditions of class, class extensions, outstanding memorandums or class recommendations? If yes, give details:	No	

1.21	If classification society changed, name of previous and date of change:		phoenix		
1.22	Does the vessel have ice class? If yes, state what level:		N/A		
1.23	Date/place of last dry-dock:		AUGUST 2024    PIRAEUS, OLP		
1.24	Date next dry dock due/next annual survey due:		AUGUST 2026	AUGUST 2025	
1.25	Date of last special survey/next special survey due:		AUGUST 2024	AUGUST 2029	
1.26	If ship has Condition Assessment Program (CAP), what is the latest overall rating:		No		
Dimensions					
1.27	Length overall (LOA):		95,50 Metres		
1.28	Length between perpendiculars (LBP):		88,85 Metres		
1.29	Extreme breadth (Beam):		15,2 Metres		
1.30	Moulded depth:		7,2 Metres		
1.31	Keel to masthead (KTM)/ Keel to masthead (KTM) in collapsed condition, if applicable:		35.02 Metres		
1.32	Distance bridge front to center of manifold:		26,6 Metres		
1.33	Bow to center manifold (BCM)/Stern to center manifold (SCM):		59 Metres	58 Metres	
1.34	Parallel body distances	Lightship	Normal Ballast	Summer Dwt	
	Forward to mid-point manifold:	25.4 Metres	28,2 Metres	29,8 Metres	
	Aft to mid-point manifold:	15,6 Metres	16,5 Metres	19,7 Metres	
	Parallel body length:	41,0 Metres	44,7 Metres	49,5 Metres	
Tonnages					
1.35	Net Tonnage:		1408.58		
1.36	Gross Tonnage/Reduced Gross Tonnage (if applicable):		2983		
1.37	Suez Canal Tonnage - Gross (SCGT)/Net (SCNT):				
1.38	Panama Canal Net Tonnage (PCNT):				
Loadline Information					
1.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	2.109 Metres	5.10 Metres	3945,0 Metric Tonnes	5764,15 Metric Tonnes
	Winter:	2.215 Metres	4,985 Metres	3844,0 Metric Tonnes	5649,0 Metric Tonnes
	Tropical:	2.003 Metres	5,197 Metres	4078,0 Metric Tonnes	5889,0 Metric Tonnes
	Lightship:	5,504 Metres	1,696 Metres	Not Applicable	1810,9 Metric Tonnes
	Normal Ballast Condition:	3,844 Metres	3,356 Metres	1941,4 Metric Tonnes	3752,3 Metric Tonnes
	Segregated Ballast Condition:				
1.40	FWA/TPC at summer draft:				
1.41	Does vessel have multiple SDWT? If yes, please provide all assigned loadlines:		N/A		
1.42	Constant (excluding fresh water):				
1.43	What is the company guidelines for Under Keel Clearance (UKC) for this vessel?		<div>- The Minimum Under Keel Clearance shall at no time be less than one point five percent (1,5%) of the vessel's extreme breadth or less than thirty centimetres (30 cm) whichever is the greater will be effective for moored vessels.</div> <div>- Once all dynamic factors have been taken into consideration, a margin of safety is at least 10% of the static draft that remains under the keel for vessels that are underway/ transiting to</div>		

		and from berth or at SBM/CBM. - A margin of safety is at least 20% of the static draft that remains under the keel for vessels that are underway in fairway, river navigation and shallow waters. - A margin of safety of at least 100% of the static draft for vessel navigating coastal waters. - A margin of safety is at least 150% of the static draft for vessels navigating at sea.	
1.44	What is the max height of mast above waterline (air draft)	Full Mast	Collapsed Mast
	Summer deadweight:	22,19 Metres	0 Metres
	Normal ballast:	23,35 Metres	0 Metres
	Lightship:	24,12 Metres	0 Metres

2.	CERTIFICATES	Issued	Last Annual	Last Intermediate	Expires
2.1	ΠΡΩΤΟΚΟΛΛΟ ΓΕΝΙΚΗΣ ΕΠΙΘΕΩΡΗΣΗΣ:	20/5/2025			11/5/2026
2.2	Safety Radio Certificate (SRC):	n/a			
2.3	Safety Construction Certificate (SCC):	n/a			
2.4	ΠΙΣΤΟΠΟΙΗΤΙΚΟ ΓΡΑΜΜΗΣ ΦΟΡΤΩΣΕΩΣ ΠΛΟΙΩΝ ΕΣΩΤΕΡΙΚΟΥ:	03/06/2025			13/5/2030
2.5	International Oil Pollution Prevention Certificate (IOPPC):	03/06/2025			13/5/2030
2.6	International Ship Security Certificate (ISSC):	n/a			
2.7	Maritime Labour Certificate (MLC):	n/a			
2.8	Interim ISM Safety Management Certificate (SMC):	27/5/22			08/05/2027
2.9	Interim Document of Compliance (DOC):	27/5/2022	17/7/2024		08/05/2027
2.10	USCG Certificate of Compliance (USCGCOC):	N/A			
2.11	Civil Liability Convention (CLC) 1992 Certificate:	Feb 04, 2025			Feb 04, 2026
2.12	Civil Liability for Bunker Oil Pollution Damage Convention (CLBC) Certificate:	Feb 04, 2025			Feb 04, 2026
2.13	Liability for the Removal of Wrecks Certificate (WRC):	Feb 04, 2025			Feb 04, 2026
2.14	U.S. Certificate of Financial Responsibility (COFR):	n/a			
2.15	Certificate of Class (COC):	n/a			
2.16	International Sewage Pollution Prevention Certificate (ISPPC):	03/06/2025			13/5/2030
2.17	Certificate of Fitness (COF):	n/a			
2.18	International Energy Efficiency Certificate (IEEC):	n/a			
2.19	International Air Pollution Prevention Certificate (IAPPC):	n/a			

Documentation		
2.20	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:	Yes
2.21	Does vessel have in place a Drug and Alcohol Policy complying with OCIMF guidelines for Control of Drugs and Alcohol Onboard Ship?	Yes
2.22	Is the ITF Special Agreement on board (if applicable)?	n/a
2.23	ITF Blue Card expiry date (if applicable):	n/a

3.	CREW
3.1	Nationality of Master: Greek
3.2	Number and nationality of Officers: 5/1 6 all Greek
3.3	Number and nationality of Crew: 15/1 15 all ratings Greek
3.4	What is the common working language onboard: Greek
3.5	Do officers speak and understand English? Yes

3.6	If Officers/ratings employed by a manning agency - Full style:	n/a	n/a
-----	--	-----	-----

<b>4.</b>	<b>FOR USA CALLS</b>		
4.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter?	N/A	
4.2	Qualified individual (QI) - Full style:	N/A	
4.3	Oil Spill Response Organization (OSRO) - Full style:	N/A	
4.4	Salvage and Marine Firefighting Services (SMFF) - Full Style:		

<b>5.</b>	<b>SAFETY/HELICOPTER</b>		
5.1	Is the vessel operated under a Quality Management System? If Yes, what type of system? (ISO9001 or IMO Resolution A.741(18) as amended):	Yes IMO Resolution A.741(18)	
5.2	Can the ship comply with the ICS Helicopter Guidelines?	N/A	
5.2.1	If Yes, state whether winching or landing area provided:	N/A	
5.2.2	If Yes, what is the diameter of the circle provided:	N/A	

<b>6.</b>	<b>COATING/ANODES</b>				
6.1	Tank Coating	Coated	Type	To What Extent	Anodes
	Cargo tanks:	Yes	EPOXY	Whole Tank	No
	Ballast tanks:	Yes	EPOXY	Whole Tank	Yes
	Slop tanks:	Yes	EPOXY	Whole Tank	No

<b>7.</b>	<b>BALLAST</b>				
7.1	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Ballast Pumps:	2	150-CW2 16	180M3/HR	30 Metres
	Ballast Eductors:				

8.	CARGO		
Double Hull Vessels			
8.1	Is vessel fitted with centerline bulkhead in all cargo tanks? If Yes, solid or perforated:	Yes,Solid	
Cargo Tank Capacities			
8.2	Number of cargo tanks and total cubic capacity (98%):	10	4409,39 Cu. Metres

8.2.1	Capacity (98%) of each natural segregation with double valve (specify tanks):		
8.3	Number of slop tanks and total cubic capacity (98%):	2	183,39 Cu. Metres
8.3.1	Specify segregations which slops tanks belong to and their capacity with double valve:	139,3CBM	
8.3.2	Residual/retention oil tank(s) capacity (98%), if applicable:	N/A	
<b>SBT Vessels</b>			
8.3.3	What is total SBT capacity and percentage of SDWT vessel can maintain?	1796,21CBM	45,5 %
8.3.4	Does vessel meet the requirements of MARPOL Annex I Reg 18.2:	Yes	
<b>Cargo Handling and Pumping Systems</b>			
8.4	How many grades/products can vessel load/discharge with double valve segregation:	3	
8.5	Are there any cargo tank filling restrictions? If yes, specify number of slack tanks, max s.g., ullage restrictions etc.:	NO	
8.6	Max loading rate for homogenous cargo	With VECS	Without VECS
	Loaded per manifold connection:		600 Cu. Metres/Hour
	Loaded simultaneously through all manifolds:		600 Cu. Metres/Hour
<b>Cargo Control Room</b>			
8.7	Is ship fitted with a Cargo Control Room (CCR)?	Yes	
8.8	Can tank innage/ullage be read from the CCR?	Yes	
<b>Gauging and Sampling</b>			
8.9	Is gauging system certified and calibrated? If no, specify which ones are not calibrated:	,	
	What type of fixed closed tank gauging system is fitted:	Radar	
	Are high level alarms fitted to the cargo tanks? If Yes, indicate whether to all tanks or partial:	Yes, All	
8.9.1	Can cargo be transferred under closed loading conditions in accordance with ISGOTT 11.1.6.6?	Yes	
8.9.2	Are cargo tanks fitted with multipoint gauging? If yes, specify type and locations:	No,	
8.10	Number of portable gauging units (example- MMC) on board:	2	
<b>Vapor Emission Control System (VECS)</b>			
8.11	Is a Vapour Emission Control System (VECS) fitted?	Yes	
8.12	Number/size of VECS manifolds (per side):	2	150 Millimetres
8.13	Number/size/type of VECS reducers:	N/A	
<b>Venting</b>			
8.14	State what type of venting system is fitted:	HIGH VELOCITY	
<b>Cargo Manifolds and Reducers</b>			
8.15	Total number/size of cargo manifold connections on each side:	PORT SIDE 2 / 8 INCHES – 1 / 6 INCHES STB SIDE 2 / 8 INCHES – 1 / 6 INCHES	
8.16	What type of valves are fitted at manifold:	Butterfly	
8.17	What is the material/rating of the manifold:	STAINLESS STEEL	
8.17.1	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment'?	N/A	
8.18	Distance between cargo manifold centers:	780 Millimetres	
8.19	Distance ships rail to manifold:	2200 Millimetres	
8.20	Distance manifold to ships side:	2300 Millimetres	

8.21	Top of rail to center of manifold:	250 Millimetres		
8.22	Distance main deck to center of manifold:	1340 Millimetres		
8.23	Spill tank grating to center of manifold:	780 Millimetres		
8.24	Manifold height above the waterline in normal ballast/at SDWT condition:	5184 Millimetres		
8.25	Number/size/type of reducers:	4 x 300/200mm (12/8") 4 x 300/250mm (12/10") 4 x 200/150mm (8/6") 3 x 150/100mm (6/4") 1 x 250/150mm (10/6") ANSI		
8.26	Is vessel fitted with a stern manifold? If yes, state size:	Yes, 250 Millimetres		
Heating				
8.27	Cargo/slop tanks fitted with a cargo heating system?	Type	Coiled	Material
	Cargo Tanks:	Steam through	Yes	SS
	Slop Tanks:	Steam through	Yes	SS
8.28	Maximum temperature cargo can be loaded/maintained:	80.0 °C		80 °C
8.28.1	Minimum temperature cargo can be loaded/maintained:	60.0 °C		60.0 °C
Inert Gas and Crude Oil Washing				
8.29	Is an Inert Gas System (IGS) fitted/operational?	N/A		
8.29.1	Is a Crude Oil Washing (COW) installation fitted/operational?	N/A/N/A		
8.30	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:	N/A		
Cargo Pumps				
8.31	How many cargo pumps can be run simultaneously at full capacity:			4
8.32	Pumps	No.	Type	Capacity
				At What Head (sg=1.0)
	Cargo Pumps:	3	2X Standart (SNK) 1x Borneman	350 M3/HR 450 m3 /HR
	Cargo Eductors:			
	Stripping:			
8.33	Is at least one emergency portable cargo pump provided?			

<b>9.</b>	<b>MOORING</b>					
9.1	Wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
9.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
9.3	Ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	48 Millimetres	polyester polypropylene	220 Metres	42 Metric Tonnes
	Main deck fwd:	2	48 Millimetres	polyester polypropylene	220 Metres	42 Metric Tonnes
	Main deck aft:	3	48 Millimetres	polyester polypropylene	220 Metres	42 Metric Tonnes

	Poop deck:	4	48 Millimetres	polyester polypropylene	220 Metres	42 Metric Tonnes
9.4	Other lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
9.5	Winches	No.	No. Drums	Motive Power	Brake Capacity	Type of Brake
	Forecastle:	2	Single	Hydraulic	43,7 Metric Tonnes	lining
	Main deck fwd:					
	Main deck aft:					
	Poop deck:	1	Double	Hydraulic	26,22 Metric Tonnes	lining
9.6	Bitts, closed chocks/fairleads		No. Bitts	SWL Bitts	No. Closed Chocks	SWL Closed Chocks
	Forecastle:		8	80 Metric Tonnes		
	Main deck fwd:		2	80 Metric Tonnes		
	Main deck aft:		2	80 Metric Tonnes		
	Poop deck:		8	80 Metric Tonnes		
<b>Anchors/Emergency Towing System</b>						
9.7	Number of shackles on port/starboard cable:				8/7	
9.8	Type/SWL of Emergency Towing system forward:				N/A	
9.9	Type/SWL of Emergency Towing system aft:				N/A	
<b>Escort Tug</b>						
9.10	What is size/SWL of closed chock and/or fairleads of enclosed type on stern:				320 x 225	30T
9.11	What is SWL of bollard on poop deck suitable for escort tug:				30T	
<b>Lifting Equipment/Gangway</b>						
9.12	Derrick/Crane description (Number, SWL and location):				1X2000 KG MAIN DECK MANIFOLD AREA 1X2000 KG BOAT DECK STERN MANIFOLD AREA	
9.13	Accommodation ladder direction:					
	Does vessel have a portable gangway? If yes, state length:					
<b>Single Point Mooring (SPM) Equipment</b>						
9.14	Does the vessel meet the recommendations in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings (SPM)'?				N/A	
9.15	If fitted, how many chain stoppers:				N/A	
9.16	State type/SWL of chain stopper(s):				N/A	
9.17	What is the maximum size chain diameter the bow stopper(s) can handle:				N/A	
9.18	Distance between the bow fairlead and chain stopper/bracket:				N/A	
9.19	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:				N/A	
<b>10. PROPULSION</b>						
10.1	Speed				Maximum	Economical
	Ballast speed:				9,25 Knots (WSNP)	9 Knots (WSNP)
	Laden speed:				8,75 Knots (WSNP)	8 Knots (WSNP)
10.2	What type of fuel is used for main propulsion/generating plant:				IFO 180 cst	LS MGO

10.3	Type/Capacity of bunker tanks:	Fuel Oil: 356,55M3 Diesel Oil: Gas Oil: 94,23M3		
10.4	Is vessel fitted with fixed or controllable pitch propeller(s):	FIXED		
10.5	Engines	No	Capacity	Make/Type
	Main engine:	1	2060kw	Guangzhou
	Aux engine:	4	3x284kw/1x105kw (emergency)	Cummins NTA 855 g2m
	Power packs:			
	Boilers:	1	3 t/h 7 bar	Wuxi chenshi Isk3- 0,7
<b>Bow/Stern Thruster</b>				
10.6	What is brake horse power of bow thruster (if fitted):	N/A		
10.7	What is brake horse power of stern thruster (if fitted):	N/A,		
<b>Emissions</b>				
10.8	Main engine IMO NOx emission standard:			
10.9	Energy Efficiency Design Index (EEDI) rating number:			

<b>11.</b>	<b>SHIP TO SHIP TRANSFER</b>		
11.1	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum, Chemicals or Liquified Gas, as applicable)?	Yes	
11.2	What is maximum outreach of cranes/derricks outboard of the ship's side:	PORT 3,8M/STB 6,2M	
11.3	Date/place of last STS operation:		

<b>12.</b>	<b>RECENT OPERATIONAL HISTORY</b>		
12.1	Last three cargoes/charterers/voyages (Last/2nd Last/3rd Last):	To be advised	
12.2	Has vessel been involved in a pollution, grounding, serious casualty, unscheduled repair or collision incident during the past 12 months? If yes, provide details:	Pollution: No, Grounding: No, Casualty: No,	
		Repair: , Collision: No,	
12.3	Date and place of last Port State Control inspection:	27.07.2013 / izmit	
12.4	Any outstanding deficiencies as reported by any Port State Control? If yes, provide details:	No	
12.5	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: * "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.	ALMA PETROLI 14/7/2025 SHELL 23/12/2024	
12.6	Date/Place of last SIRE inspection:	14/7/2025 aspropyrgos	
12.7	Additional information relating to features of the ship or operational characteristics:		

Revised 2018 ([INTERTANKO/Q88.com](http://www.intertanko.com))